

RECEIVED  
CENTRAL FAX CENTER

FEB 27 2006

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent No. 6,955,278	:	
Inventor: Willy Lorscheidt	:	Group Art Unit 3754
Issued: October 18, 2005	:	Examiner F. C. Nicolas
For: DISPENSER FOR PASTY PRODUCTS	:	Docket No. 19559

REQUEST FOR ISSUANCE OF A CORRECTED PATENT  
UNDER 37 C.F.R. § 1.322 (b)

Commissioner for Patents  
P. O. Box 1450  
Alexandria, VA 22313-1450

Sir:

In accordance with the provisions of 37 C.F.R. § 1.322(b), Applicant requests that a corrected patent be issued owing to a mistake on the part of the office such that a certificate of correction is deemed inappropriate in form.

More particularly, it is noted that many errors are contained in the claims of the printed patent, including at least patent claims 1, 12, 13, 16, and 17. The patent claims do not correspond with the allowed claims as amended by the Examiner's Amendment that accompanied the Notice of Allowance dated April 28, 2006.

To correspond with the Examiner's Amendment, the amended claims should read as follows:

1. A dispenser for dispensing a paste-like product, comprising:

(a) a generally cylindrical hollow container (1) having a vertical longitudinal axis (X) and upper and lower ends, said container including intermediate said ends a transverse wall (10) that defines in said container a lower chamber (10a) for receiving the paste-like product, and an upper delivery chamber (100) having a cylindrical wall defined on an inner sleeve portion (13) of said container, said lower chamber containing a vertically displaceable follower piston (22), said transverse wall containing a discharge opening (11) containing valve means (20)

Best Available Copy

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322(b)  
Filed February 2, 2006

that permit the flow of a variable volume of the paste-like product from said lower chamber to said upper delivery chamber when the pressure of said lower chamber exceeds that of said upper chamber;

(b) a generally cylindrical main headpiece (3) arranged above said transverse wall for vertical displacement relative to said container, said headpiece having upper and lower ends, said lower end containing an internal chamber having a top wall (35), said internal chamber having an inner cylindrical side wall that defines bushing means (31), said headpiece containing at said upper end a laterally extending product discharge channel (32) in communication with said internal chamber;

(c) a generally cylindrical vertically arranged delivery piston (5) arranged for vertical sliding movement relative to said container, said piston having an upper end (50) that extends within said headpiece internal chamber and terminates in an upper end wall (54), said piston having a lower end (52) that is in sliding engagement with said delivery chamber cylindrical wall, said piston containing a vertical longitudinal delivery channel (50a) having a lower end containing an inlet opening (53) in communication with said delivery chamber, said delivery piston upper end containing at least one radial outlet opening (58) in communication with said longitudinal delivery channel; and

(d) spring means (7) biasing said headpiece upwardly toward a first position relative to said container;

(e) said delivery piston having a first position relative to said container such that when said main headpiece is in said first position, the upper end of said delivery piston is spaced by a given axial distance (a) from said main headpiece upper wall, and said delivery piston outlet opening is closed by an upper first surface portion (31b) of said bushing means;

(f) said main headpiece being longitudinally displaceable downwardly relative to said

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322(b)  
Filed February 2, 2006

container and said piston toward a second position in which said headpiece top wall engages said piston upper wall, and said bushing means first surface portion is displaced to an open position relative to said delivery piston outlet opening;

(g) said headpiece being downwardly displaceable from said second position toward a third position relative to said container, thereby causing said piston to be displaced by said headpiece to a second position relative to said container, whereby the pasty-like product is pumped from said delivery chamber to said product discharge channel via said piston longitudinal discharge channel and said piston outlet opening.

2. The dispenser according to claim 1, characterized in that the headpiece bushing means includes a lower second bushing surface portion (31a) which guides the delivery piston in a longitudinally displaceable manner and which comprises at least one guide surface cooperating with the circumferential surface of the delivery piston.
3. The dispenser according to claim 1, characterized in that the headpiece (3) and the delivery piston have provided thereon entraining means (34, 57) by which the delivery piston is entrained after manual operation during resetting of the headpiece (3) into the initial first position.
4. The dispenser according to claim 3, characterized in that said entraining means includes an entraining shoulder (67) which cooperates with an entraining rim (34) formed on the delivery piston.
5. The dispenser according to claim 4, characterized in that the entraining shoulder (34) is provided at the end side on the bushing means (31) at the transition to the discharge channel (32), and the entraining rim (57) is provided in the end portion of the delivery shaft (50) at the front side.
6. The dispenser according to claim 1, characterized in that the delivery piston (51) projects

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322(b)  
Filed February 2, 2006

radially outwardly to define an annular contact surface (51a), and that the guide bushing means (31) has a pressure end surface (33) that is arranged in the initial position at said given axial distance relative to the annular contact surface (51a) and is positioned by axial displacement of the headpiece (3) toward the container (1) on the annular contact surface (51a).

7. The dispenser according to claim 1, characterized in that the inner wall of the delivery chamber (100) is formed by the inner sleeve portion (13) of the container (1) adjacent the headpiece (3).

8. A dispenser for dispensing a paste-like product, comprising:

(a) a generally cylindrical hollow container (1) having a vertical longitudinal axis (X) and upper and lower ends, said container including intermediate said ends a transverse wall (10) that defines in said container a lower chamber (10a) for receiving the paste-like product, and an upper delivery chamber (100) having a cylindrical wall defined on an inner sleeve portion (13) of said container, said lower chamber containing a vertically displaceable follower piston (22), said transverse wall containing a discharge opening (11) containing valve means (20) that permit the flow of a variable volume of the paste-like product from said lower chamber to said upper delivery chamber when the pressure of said lower chamber exceeds that of said upper delivery chamber;

(b) a generally cylindrical main headpiece (3) arranged above said transverse wall for vertical displacement relative to said container, said headpiece having upper and lower ends, said lower end containing an internal chamber having a top wall (35), said internal chamber having an inner cylindrical side wall that defines bushing means (31), said headpiece containing at said upper end a laterally extending product discharge channel (32) in communication with said internal chamber;

(c) a generally cylindrical vertically arranged delivery piston (5) arranged for vertical sliding

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322 (b)  
Filed February 2, 2006

movement relative to said container, said piston having an upper end (50) that extends within said headpiece internal chamber and terminates in an upper end wall (54), said piston having a lower end (52) that is in sliding engagement with said delivery chamber cylindrical wall, said piston containing a vertical longitudinal delivery channel (50a) having a lower end containing an inlet opening (53) in communication with said delivery chamber, said delivery piston upper end containing at least one radial outlet opening (58) in communication with said longitudinal delivery channel;

(d) spring means (7) biasing said headpiece upwardly toward a first position relative to said container;

(e) said delivery piston having a first position relative to said container such that when said main headpiece is in said first position, the upper end of said delivery piston is spaced by a given axial distance (a) from said main headpiece upper wall, and said delivery piston outlet opening is closed by an upper first surface portion (31b) of said bushing means;

(f) said main headpiece being longitudinally displaceable downwardly relative to said container and said piston toward a second position in which said headpiece top wall engages said piston upper wall, and said bushing means first surface portion is displaced to an open position relative to said delivery piston outlet opening;

(g) said headpiece being downwardly displaceable from said second position toward a third position relative to said container, thereby causing said piston to be displaced by said headpiece to a second position relative to said container, whereby the pasty-like product is pumped from said delivery chamber to said product discharge channel via said piston longitudinal discharge channel and said piston outlet opening, and

(h) a generally cylindrical mating headpiece (4) connected with said container for guiding said main headpiece, said mating member having an outer holding cylindrical portion (41) arranged concentrically about said container inner sleeve portion, and an inner tubular guide

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322(b)  
Filed February 2, 2006

portion (42) arranged concentrically within said sleeve portion for guiding the sliding displacement of the headpiece (3).

9. The dispenser according to claim 8, characterized in that the end of the guide portion (42) at the delivery chamber cylindrical wall comprises a delivery piston stop (42a) for the delivery piston (5).

10. The dispenser according to claim 8, characterized in that the holding cylinder (41) is provided with an annular shoulder (44) at the bottom side which forms a contact surface for a coil spring holding the headpiece in the initial position under bias and is put on the front side of the container (1).

11. The dispenser according to claim 8, characterized in that the mating headpiece (4) comprises at least one stop (46a) for defining the axial displacement movement of the headpiece (3) and is formed together with the headpiece (3) as a prefabricated dispenser component and is fastened at the front side to the container (1).

12. The dispenser according to claim 11, characterized in that the dispenser component is locked with the container (1) via locking means (47; 17) formed on the mating headpiece (4) and the front side of the container (1).

13. The dispenser according to claim 1, characterized in that the headpiece (3) is longitudinally displaceable such that the headpiece (10) can be brought by manual operation from the initial position first by a first axial distance (a) for contact with the delivery piston with simultaneous exposure of the delivery channel outlet opening (58) in the discharge channel (32) into a central position (M) and the headpiece (3) can then be brought with a progressive axial displacement with entrainment of the delivery piston (51) from the central position (M) into a discharge end position (V) in which the delivery chamber (100) has reached a minimum volume by displacement of the delivery piston (51).

L:\LARRY.SR\APPLICAT\19559\REQUESTFOR ISSUANCE.DOC

6

Request for Issuance of Corrected Patent  
Under 37 C.F.R. §1.322(b)  
Filed February 2, 2006

14. The dispenser according to claim 1, characterized by a closure member (60) which is fixed to the headpiece and by which a product discharge opening (39) of the discharge channel (32) can be closed.

15. The dispenser according to claim 14, characterized in that the product discharge opening (39) is formed as a ring around a closure mandrel (32a) arranged in the discharge channel, and that the closure member (60) has an annularly formed sealing lip which can sealingly be placed on the closure mandrel.

16. The dispenser according to claim 14, characterized in that the closure member (60) is made from a flexible plastic material, preferably from a thermoplastic elastomer.

17. The dispenser according to claim 14, characterized in that the closure member (60) is integral with a coating (61) formed at least at the front side on the outside of the headpiece (3).

Since the nature of the printing errors on the part of the Office is such that a certificate of correction is believed to be inappropriate in form, the Patentee respectfully requests that the Director issue a corrected patent. Patentee hereby offers to return the original Letters Patent No. 6,955,278.

Favorable action is courteously solicited.

2/27, 2006

Respectfully submitted,



Lawrence E. Laubscher, Sr.

Customer No. 26480

Registration No. 18,202

Laubscher & Laubscher, P.C.

Suite 2B

1160 Spa Road

Annapolis, Maryland 21403

Telephone: (703) 521-2660